







Model	Wireless	Outdoor / Indoor	Image Sensor	Video Modulation	Minimum Illumination	Auto-iris	Lens Type	Max Video Resolution	Frames per Second	Networking	Digital Input / Output	Audio Capability	Video Compression	Multiple Streams	PoE	Value-added Features
 PZ71X2	802.11b/g	Indoor	1/4 inch CCD	NTSC/PAL	0.5 Lux @ F1.8 0.05 Lux @ F1.8 (Low light mode)	Yes	10x optical zoom 4.2 ~ 42 mm F1.8(w), 2.9(t)	704x480/ NTSC 704x576/PAL	Up to 30/NTSC Up to 25/PAL	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/ MPEG-4)	Dual	-	-
 PZ71X1	-	Indoor	1/4 inch CCD	NTSC/PAL	0.5 Lux @ F1.8 0.05 Lux @ F1.8 (Low light mode)	Yes	10x optical zoom 4.2 ~ 42 mm F1.8(w), 2.9(t)	704x480/ NTSC 704x576/PAL	Up to 30/NTSC Up to 25/PAL	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/ MPEG-4)	Dual	Yes	-
 PZ7152	802.11b/g	Indoor	1/4 inch progressive CCD	-	0.5 Lux @ F1.9	Yes	2.6x optical zoom 2.8 ~ 7.3 mm F1.9	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/ MPEG-4)	Dual	-	-
 PZ7151	-	Indoor	1/4 inch progressive CCD	-	0.5 Lux @ F1.9	Yes	2.6x optical zoom 2.8 ~ 7.3 mm F1.9	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	1 / 1	Yes (2-way audio)	Dual-Codec (MJPEG/ MPEG-4)	Dual	Yes	-
 PT7137	802.11b/g	Indoor	1/4 inch CMOS	-	1.5 Lux @ F2.0	-	4.0 mm, F2.0 Fixed	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	-	Yes	MPEG-4	-	-	-
 PT7135	-	Indoor	1/4 inch CMOS	-	1.5 Lux @ F2.0	-	4.0 mm, F2.0 Fixed	640x480	Up to 30/60Hz Up to 25/50Hz	10/100 BaseT Ethernet	-	Yes	MPEG-4	-	-	-